ELSEVIER

Artificial Intelligence 137 (2002) 279

Artificial Intelligence

www.elsevier.com/locate/artint

Author Index—Volume 137 (2002)

Aiolli, F. and A. Sperduti
A re-weighting strategy for improving margins 197–216
Bell, D., see Cheng, J. 43– 90
Cheng, J., R. Greiner, J. Kelly, D. Bell and W. Liu
Learning Bayesian networks from data: An information-theory based approach 43– 90
Gerevini, A. and J. Renz
Combining topological and size information for spatial reasoning 1– 42
Greiner, R., see Cheng, J. 43– 90
Kelly, J., see Cheng, J. 43– 90
Lamperti, G. and M. Zanella
Diagnosis of discrete-event systems from uncertain temporal observations 91–163
Liu, W., see Cheng, J. 43– 90
Raphael, C.
A hybrid graphical model for rhythmic parsing 217–238
Renz, J., see Gerevini, A. 1– 42
Shoham, Y. and S. Toledo
Parallel Randomized Best-First Minimax Search 165–196
Sperduti, A., see Aiolli, F. 197–216
Tang, W., see Zhou, Z.-H. 239–263
Toledo, S., see Shoham, Y. 165–196
Wu, J., see Zhou, Z.-H. 239–263
Zanella, M., see Lamperti, G. 91–163
Zhou, Z.-H., J. Wu and W. Tang
Ensembling neural networks: Many could be better than all 239–263

0004-3702/2002 Published by Elsevier Science B.V.
PII: S0004-3702(02)00217-5